

# Declaration on materials and the environment

Product	Туре	VUE015150, PN 16/10		
	Description	Flanged through valve		
	Range	Valves		
Process supervisor	Fr. Sauter Ltd. Im Surinam 55, CH-4016 Basle			
	Management system certified ISO 9001 ISO 9001:2000 ISO 14001:2004 OHSAS 18001:1999	since by 10 <sup>th</sup> Aug. 1993 SQS 10 <sup>th</sup> Aug. 2002 SQS 10 <sup>th</sup> Aug. 2005 SQS 10 <sup>th</sup> Aug. 2005 SQS		
Environmentally-compatible product design	Based on	Management system Fr. Sauter Ltd.		
	Process	Business process Product innovation		
Product usage	Typical energy consumption p.a.	not applicable		
	CE conformity	PDS 76.115		
	Servicing, maintenance	PDS 76.115 (no servicing req'd)		
	How the environment benefits	see last page		
Risk to the environment in the event of damage	Fire protection as per	EN 60695-2-11, EN 60695-10-2		
	Fire load <sup>(1)</sup>	max. 0.4 MJ		
	Parts containing halogen (causing corrosive smoke)	not applicable		
	Pollutive liquids	Lubricant		
	Explosive substances	none		
Packaging*	Packaging Paper PAP 22	Wooden pallet, cardboard 5 g		
	(1) See <b>Remarks</b> on last page			

\*Directive 94/62/EC and follow-up document; decision 97/129/EC

					1012 1 011 1 012
Materials		Total weight of product (2)	2,90070,000 g	Safety data sheet	EU waste code**
Synthetics					
EPDM	(O-rino	gs)	38 g	Yes	20.01.39
PTFE	(wiper)		15 g	Yes	20.01.39
PE	(protective cap + plugs, for transport only)		4130 g	Yes	20.01.39
Metal					
Grey cast iron		(housing)	2,10063,000 g	Not required	20.01.40
Cr-Ni steel			30260 g	Not required	20.01.40
Steel			251,900 g	Not required	20.01.40
Red bronze	)	(plug DN65DN150)	1,0704,500 g	Not required	20.01.40
Brass		(stuffing box; plug up to DN50)	1001,153 g	Not required	20.01.40
Printed circui	t board				
none					
Miscellaneou	s				
-					
Special comp	onents				
Lubricant (silicone-free)		3 g	Yes	20.01.26	

### N.B.:

The valves contain no materials that are harmful to the environment.

<sup>\*\*</sup>Directive 75/442/EEC and follow-up document; decision 2001/118/EC

### **Disposal**



#### **Product:**

The valves can be completely recycled as metal waste. Fr. Sauter Ltd. observes the European directive 2002/95/EG (RoHS); the company's soldered products have been lead-free since 01.07.2006. Special treatment of particular components may, under certain

circumstances, be either compulsory by law or ecologically advisable.

#### Packaging:

Easily recyclable

Observe local regulations and the latest applicable laws.

#### Special notes:

- Observe operating temperature; risk of scalding
- Replace spare parts only when the valve is not under pressure
- Observe instructions on mounting drawing

#### Remarks

<sup>(1)</sup> Fire load, depending on type:		
VUE 015 F300	0.4 MJ	
VUE 150 F300	0.3 MJ	
Accessories:		
- 0378284 100 Stuffing-box heater complete 230V~	0.6 MJ	
- 0378284 102 Stuffing-box heater complete 24V~	0.6 MJ	
<sup>(2)</sup> Weight, depending on type:		
VUE 015 F300	2,900 g	
VUE 015 F310F330	2,960 g	
VUE 015 F340, F350	2,920 g	
VUE 020 F300	3,810 g	
VUE 025 F300	4,370 g	
VUE 032 F300	6,910 g	
VUE 040 F300	8,230 g	
VUE 050 F300	10,810 g	
VUE 065 F300	19,900 g	
VUE 080 F300	24,500 g	
VUE 100 F300	33,000 g	
VUE 125 F300	48,000 g	
VUE 150 F300	70,000 g	
Accessories:		
- 0378284 100 Stuffing-box heater complete 230V~	76 g	
- 0378284 102 Stuffing-box heater complete 24V~	69 g	

# How the environment benefits

- These heavy-duty valves have an extremely long serviceable life and require no maintenance
- Saves energy on heating and cooling due to good regulability of the flow
- Optimum use of raw materials

## Disclaimer: This declaration is solely for information purposes.

If circumstances arise, Sauter may change the above-mentioned specifications without prior notice.

Fr. Sauter Ltd. expressly rejects any liability for damage occurring due to the above information.

Further information on environmental aspects in general and on disposal in particular can be obtained from the local Sauter agent.